



12815 NE 124th St STE#D, Kirkland, WA-98034

MT40A512M16TB-062E:R vs AS4C512M16D4B-62BCN Comparison

Part Number & result Parameter	MT40A512M16TB-062E:R	AS4C512M16D4B-62BCN	Comparison Result
Product Description	DDR4 SDRAM	DDR4 SDRAM	Same
Die	Micron Die, Rev.R	Micron Die, Rev.R	Same
Capacity	8Gb (512M x 16)	8Gb (512M x 16)	Same
Memory Organization	64Meg, x16bits, x8 banks	64Meg, x16bits, x8 banks	Same
Operating Power Supply	V _{DD} & V _{DDQ} = 1.2V (+/- 60mV)	V _{DD} & V _{DDQ} = 1.2V (+/- 60mV)	Same
	V _{pp} = 2.5V (-125mV,+250mV)	V _{pp} = 2.5V (-125mV,+250mV)	Same
Operating Temperature	Commercial (0°C ≤ T _c ≤ +95°C)	Commercial (0°C ≤ T _c ≤ +95°C)	Same
Max Clock Frequency	1600 MHz	1600 MHz	Same
Min. Cycle Time	0.625ns	0.625ns	Same
Max Data Rate	3200 Mbps	3200 Mbps	Same
CAS Latency	22	22	Same
tAA(ns)	13.75	13.75	Same
tRCD (ns)	13.75	13.75	Same
tRP (ns)	13.75	13.75	Same
Number of Bank groups	2	2	Same
Bank Count per Group	4	4	Same
Row Addressing	64K (A0..A15)	64K (A0..A15)	Same
Column Addressing	1K (A0..9)	1K (A0..9)	Same
Page Size per bank	1KB	1KB	Same
Temperature controlled Refresh time	8192 Cycles at T _c range 64ms at 0C ~ 85C 32ms at 85C ~ 95C	8192 Cycles at T _c range 64ms at 0C ~ 85C 32ms at 85C ~ 95C	Same
Low Power Auto Self Refresh support	Yes	Yes	
I/O Capacitance	CIO = 1pF Max	CIO = 1pF Max	Same
Pin to Pin Compatible	Pin to Pin Compatible		
AC/DC Characteristics	Same		Meet JEDEC



12815 NE 124th St STE#D, Kirkland, WA-98034

IDD Specification			
Parameter	MT40A512M16TB-062E:R	AS4C512M16D4B-62BCN	Comparison Result
IDD Spec conditions	0C to 95C	0C to 95C	
I _{DD0} (mA) , I _{pp0} (mA)	59, 5	59, 5	Same
I _{DD1} (mA)	69	69	Same
I _{DD2N} (mA)	38	38	Same
I _{DD2NT} (mA)	46	46	Same
I _{DD2P} (mA)	30	30	Same
I _{DD2Q} (mA)	34	34	Same
I _{DD3N} (mA)	44	44	Same
I _{DD3P} (mA)	34	34	Same
I _{DD4R} (mA)	176	176	Same
I _{DD4W/A/B} (mA)	138	138	Same
I _{DD6N} (mA)	32	32	Same
I _{DD6R} (mA)	19	19	Same
I _{DD6E} (mA)	52	52	Same
I _{DD7} (mA)	225	225	Same
Package	96b FBGA 7.5x13x1.2mm	96b FBGA 7.5x13x1.2mm	Same
Solder Ball material Composition	SAC305 (96.5% Sn, 3% Ag, 0.5% Cu).	SACQ (92.45% Sn, 4% Ag, 0.5% Cu, 3% Bi, 0.05% Ni).	Different. Alliance better.
Package Material	Pb and Halogen Free	Pb and Halogen Free	Same