

Reliability Qualification Report

for

**64GB, 128GB, 256GB, 512GB
eMMC 5.1
with Pb/Halogen Free**

This information contained herein is for reference only. Alliance reserves the right to make changes to any products and/or services listed in this document, at any time without prior notice. Alliance does not assume any responsibility or liability that may arise as a result of the application, or use of any product or service described herein, except as in those cases where it has been expressly agreed to in writing by Alliance. The purchase, lease, or use of a product or service from the Alliance does not convey a license under any patent rights, copyrights, trademark rights, or any other of Alliance's, or third parties', intellectual property rights. All sales are subject to the Alliance's standard terms.

Warning: Operating under any Conditions beyond those listed as the absolute maximum limits will destroy or damage the products. In addition, operating any product for sustained periods under conditions at or near the limits of the operating ranges will stress and may temporarily (and/or permanently) affect and/or damage the product's performance, and/or functions, and/or product life.

Contents

1. Test result summary

2. Product Description

3. Package Level Test

- 3.1 High Temperature Operating Life Test(HTOL)
- 3.2 High Temperature Storage Life Test(HTSL)
- 3.3 Pre-condition Test
- 3.4 Unbiased High Acceleration Stress Test(UHAST)
- 3.5 Temperature Cycle Test(TCT)

4. ESD and Latch-Up Test

- 4.1 ESD-HBM/CDM Test
- 4.2 Latch-Up Test

5. Recommend reflow profile for Lead free Product

1. Test Result Summary

One lot submit to qualification tests according to Alliance's qualification plan. A summary of the test result is listed as follows.

Test Item		Criteria	Test Result
Package Level	HTOL	1000 hrs	PASS
	HTSL	1000 hrs	PASS
	Pre-condition	MSL-3	PASS
	UHASt	96 hrs	PASS
	TCT	500 cycles	PASS

2. Product Description

Part Number	ASFC64G31T5A-51BIN ASFC128G32T5A-51BIN ASFC256G34T5A-51BIN ASFC512G38T5A-51BIN
Process	40nm LP process
Package Type	153-TFBGA (11.5x13 mm) MCMBGA
Lot No	Specified in each test item
Flash Type	BiCS5_64GB_TLC (SBDK flash)

3. Package Level

3.1 High Temperature Operating Life Test (HTOL):

3.1.1 Purpose :

The HTOL test is to evaluate the endurance of devices when they are submitted to electrical stress and thermal stress over an extended time period.

3.1.2 Test Condition ; JEDEC JESD22-A108

Ambient temperature = 125 °C

Vccmax = 1.1X Vcc

Test duration = 1000 hrs

3.1.3 Test Result : PASS

Lot No	Result	Failure Rate(λ)	MTTF(years)
APAM530.00	0/77	153	747.5

Criteria : Based on CL = 60% and Activation Energy = 0.7eV

Acceleration factor AF = AFT * AFV = 77.94(Tj=125°C-55°C)

Chi-Square Distribution:60% Confidence

3.2 High Temperature Storage Life Test (HTSL):

3.2.1 Test Condition : JEDEC JESD22-A103

High ambient temperature = 150 °C

Test duration = 1000 hrs

3.2.2 Test Result : PASS

Lot No	Result	Remark
APAM530.00	0/45	N/A

3.3 Pre-condition Test (MSL-3):

3.3.1 Purpose :

The pre-condition test is to measure the resistance of SMDs (Surface Mounting Devices) to the storage environment at the customer site and to thermal stress created by IR reflow or Vapor Phase Reflow.

3.3.2 Test Condition : JEDEC JESD 22-A113

3.3.2.1 External Visual & Function Test

3.3.2.2 SAT Inspection

3.3.2.3 Temperature Cycle (-65 °C/150 °C, 5 cycles)

3.3.2.4 Baking (125 °C, 24 hours)

3.3.2.5 Temp & Humidity Soaking (30°C/60% RH, 192 hours)

3.3.2.6 IR Reflow * 3

3.3.2.7 External Visual & Function Test

3.3.2.8 SAT Inspection

3.3.3 Test Result : PASS

Lot No	Result	Remark
APAM530.00	0/90	N/A

Criteria : Acc/Rej = 0/1

3.4 Unbiased High Acceleration Stress Test(UHAST)

3.4.1 Purpose :

The UHAST is designed to determine the moisture resistance of devices by subjecting them to high steam pressure levels. This test is only performed on plastic/epoxy encapsulated devices and not on hermetic packages.

3.4.2 Test Condition : JEDEC JESD 22-A118

Ambient temperature = 130 °C

Ambient humidity = 85% RH

Test duration = 96 hrs

3.4.3 Test Result : PASS

Lot No	Result	Remark
APAM530.00	0/45	N/A

Criteria : Acc/Rej = 0/1

3.5 Temperature Cycling Test (TCT):

3.5.1 Purpose :

The TCT test is provided to evaluate the structural endurance of semiconductor devices when they are exposed to high and low temperature conditions, and their endurance when they are exposed to repeated temperature variation cycles from high temperature to low temperature by circulating air.

3.5.2 Test Condition : MIL-STD 883D-1010.7, JEDEC JESD22-A104

High temperature = 150 °C

Low temperature = -65 °C

Test duration = 500 cycles

3.5.3 Test Result : PASS

Lot No	Result	Remark
APAM530.00	0/45	N/A

Criteria : Acc/Rej = 0/1

4. ESD and Latch-Up Tests:

4.1 ESD-HBM/CDM Test:

4.1.1 Purpose :

The ESD test is to evaluate the immunity of semiconductor devices against static electricity to which they are exposed during their handling.

4.1.2 Test Condition : MIL-STD-883 (HBM)

JEDEC JESD22-C101 (CDM)

4.1.

Model	Lot No	Result	Remark
HBM	APAM530.00	PASS	All test pins $\geq \pm 2KV$
CDM	APAM530.00	PASS	All test pins $\geq \pm 500V$

Criteria : Acc/Rej = 0/1

4.2 Latch-Up Test:

4.2.1 Purpose :

The latch-up test is to evaluate the immunity of semiconductor devices (mainly CMOS devices) to "latch-up" that is a temporary short-circuiting between the power source and the ground caused by electrical noise coming from I/O and power supply pins of a device through two parasitic bipolar structures before a power supply is removed.

4.2.2 Test Condition : JEDEC JESD78

4.2.3 Test Result : PASS

Test Item	Lot No	Result	Remark
Trigger Current	APAM530.00	PASS	$\geq \pm 200mA$
Over Voltage Test	APAM530.00	PASS	$\geq 1.5X VCC$

Trigger Criteria : Acc/Rej = 0/1, |Spec| : $\geq \pm 200mA$

Over Voltage Test: $\geq 1.5X VCC$

5. Recommend reflow profile for Lead free Product:

5.1 Condition:

Follow: IPC/JEDEC J-STD-020

Average ramp-up rate (217°C to peak): 3 °C/sec. max

Preheat : 150~200°C · 60~120 seconds

Temperature maintained above 217°C 60~150 seconds

Time within 5°C of actual peak temperature: 30 seconds

Peak temperature : 260±0°C

Ramp-down rate: 6°C/sec. Max.

Time 25°C to peak temperature: 8 minutes max.

Cycle interval: 5 minutes

