



GD25Q16CTJGR vs AS25F316MQ-10S1INTR Comparison

Features / Parameters	GD25Q16CTJGR	AS25F316MQ-10S1INTR	Comments
Manufacturer/Supplier	GIGADEVICE	ALLIANCE MEMORY	
Product	Serial NOR FLASH Memory	Serial NOR FLASH Memory	Same
Density	16Mb	16Mb	Same
SPI	x1, x2, x4 (Standard/Dual/Quad SPI)	x1/x2/x4 (Standard/Dual/Quad SPI)	Same
Architecture	2K Byte Uniform Sector of 4K Byte Uniform Block of 32/64K Byte 256 Bytes per Programmable Page	2K Byte Uniform Sector of 4K Byte Uniform Block of 32/64K Byte 256 Bytes per Programmable Page	Same
Power Supply	2.7V~3.6V	2.7V~3.6V	Same
Cout Capacitance (Max.)	8pF	8pF	Same
Speed (Max)	120MHz Fast read with 30pf load Dual IO Data Transfer upto 240Mbps Quad IO Data Transfer upto 480Mbps	104MHz Fast read with 30pf load Dual IO Data Transfer upto 208Mbps Quad IO Data Transfer upto 416Mbps	Giga better
Page Program Time	2.4ms (Max.)	2ms (Max.)	Alliance better
Sector Erase Time (4KB)	300ms (Max.)	10ms (Max.)	Alliance better
Block Erase Time(64KB)	2s (Max.)	10ms (Max.)	Alliance better
Chip Erase Time	20s (Max.)	10ms (Max.)	Alliance better
Erase/Program cycles	Min.100,000 cycles	Min.100,000 cycles	Same
Data Retention	20years Typical	20years Typical	Same
Protection	S/W, H/W Lock/Write Protect	S/W, H/W Lock/Write Protect	Same
OTP	4x256 Byte Security registers with OTP locks	4x256 Byte Security registers with OTP locks	Same
Deep PowerDown current	1uA (Typical), 5uA (Max.)	0.65uA (Typical), 22uA (Max.)	Giga better
Standby Current	1uA (Typical)	8uA (Typical)	Giga better
Package	8pin SOP (150mils)	8pin SOP (150mils)	Same
Operating Temperature	-40C~105C Extended Industrial Grade	-40C~85C Industrial Grade	Giga wider
Compliance	ROHS and Halogen Free	ROHS an Halogen Free	Same
Pin to Pin compatibility	Yes 	Yes 	Same